




Rev.	Description.	Date	App.
01			














RECOMMENDED P.C.B LAYOUT(TOLERANCE:±0.05 TOP VIEW)


SOLDER AREA KEEP OUT AREA CONNECTOR AREA

NOTES:

1.MATERIAL:
- HOUSING: LCP, UL94V-0, BLACK
- CONTACT: COPPER ALLOY
- SHELL: STAINLESS STEEL

2.FINISH:
- CONTACT:
  - CONTACT AREA: G/F GOLD PLATED
  - SOLDER AREA: G/F GOLD PLATED
  - UNDER PLATING: NICKEL PLATED
- SHELL:
  - SOLDER AREA: G/F GOLD PLATED
  - UNDER PLATING: NICKEL PLATED

3.SPECIFICATION:
- CURRENT RATING: 1A / (1PIN)
- VOLTAGE RATING: 50V AC/DC
- DIELECTRIC WITHSTANDING: 500V AC FOR 1 MINUTE
- CONTACT RESISTANCE: 30mΩ MAX.
- INSULATION RESISTANCE: 1000MΩ MIN.
- OPERATING TEMPERATURE: -40°C ~ +85°C
- DURABILITY: 10,000 CYCLES MIN.
- CONTACT RETENTION: 2.5N MIN.
- INSERTION FORCE: 10N MAX.
- WITHDRAWAL FORCE: 10N



MICRO SIM CARD

SIM PIN ASSIGNMENT	
PIN NO.	NAME
C1	VCC
C2	RST
C3	CLK
C4	RESERVED
C5	GND
C6	VPP
C7	I/O
C8	RESERVED

研騰國際企業股份有限公司
YANNIS ELECTRONICS CO.,LTD.

PROJECTION:	UNIT: mm	GENERAL TOLERANCES: .X ±0.30 X° ± 3° .XX ±0.20 .X° ± 1° .XXX ±0.10	APPROVED	David	SHEET: 1 OF 1	REV.: A	NAME	Micro SIM Push-Pull Type 6 Pin H:1.48mm	
	SCALE: Free		CHECKED	Sunny					
			DRAWN	Juno	DATE: 2021/05/28		PART NO.	MSIM-0104060	DWG NO. MSIM-0104060_01