
Rev.	Description.	Date	App.
01			



NOTES: TYPICAL SPECIFICATIONS

1.0. ELECTRICAL DATA
- 1.1. FREQUENCY RANGE : DC 6 GHz
- 1.2. IMPEDANC : 50 Ohms
- 1.3. VSWR : < 1.35
- 1.4. DIELECTRIC WITHSTANDING VOLTAGE : 500 Vrms
- 1.5. WORKING VOLTAGE : 170 Vrms max.
- 1.6. INSULATION RESISTANCE : 1000 Mega-Ohms
- 1.7. CENTER CONTACT RESISTANCE : 6.0 mini-Ohms
- 1.8. OUTER CONTACT RESISTANCE : 4.0 mini-Ohms

2.0. MECHANICAL DATA
- 2.1. COUPLING METHOD : Threaded
- 2.2. DURABILITY (MATING/ UNMATING) : 500 Cycles
- 2.3. COUPLING NUT RETENTION : 60 ibs
- 2.4. MATING TORQUE : 10 in-ibs max.

Item/N	Material	Finish
Insulator	Teflon	
Conductor	Brass	Gold
Body	Brass	Gold

研騰國際企業股份有限公司
YANNIS ELECTRONICS CO.,LTD.

PROJECTION:	UNIT: mm	GENERAL TOLERANCES: .X ±0.38 X°. ±3° .XX ±0.25 .X° ±2° .XXX ±0.15	APPROVED	David	SHEET: 1 OF 1	REV.: A	NAME	SMA JACK TO SMB JACK ADAPTOR
	SCALE: Free		CHECKED	Sunny				
			DRAWN	Juno	DATE: 2021/01/27		PART NO.	ADPT-AB321JJ-01 DWG NO. ADPT-AB321JJ-01_01